

APPENDIX A, SHELTER PRODUCT DATA SHEET, REVISION A:

PRODUCT DATA SHEET		CONTRACTOR NAME: CAMSS Shelters						
1.PART NUMBER: CAMSS-HIT-20Q19-HUB-T 2.NSN:								
3.NAME: CAMSS20Q HUB		4.TYPE: Complexing Shelter			5.CLASS:			
6.COLOR: 595 TAN		7. Support System: Frame			8.SERIES: CAMSS20	Q		
9. INTENDED USE: Command Posts – Connects multiple command posts and briefing shelters together.								
10.DIMENSIONS (IN FEET AND INCHES)	LENGTH: 19'		WIDTH: 20'		HEIGHT: RIDGE/EAV 10' Peak Height	/E:		
11.DIMENSIONS (EXTERNAL GUYED)	LENGTH: 19'		WIDTH 26'					
12.SQUARE FEET INTERIOR: 598 Square Feet								
13.WEIGHT (POUNDS, UNPACKAGED) 550 lbs			14.WEIGHT (PACKAGED) 850 lbs		15.SHIPPING CUBE (PACKAGED) 75 cu. f	t		
16SHIPPING CONTAINER	LENGTH: 1	02"	WIDTH: 44"		HEIGHT: 20"			
17.SET-UP TIME/ NUMBER OF PERSONS 15 minutes/4 persons			18.STRIKE TIME/ NUMBER OF PERSONS: 10 minutes/4 persons					
19.PARTS INCLUDED. Included with the CAMSS20Q19-HUB is the 2" x 2" aluminum frame and the tensioned								

19.PARTS INCLUDED. Included with the CAMSS20Q19-HUB is the 2" x 2" aluminum frame and the tensioned MIL Spec cover system. The HUB also includes a fabric floor. Also included is an anchoring package with double headed spikes, guy spikes and guy ropes and a repair kit. The complete CAMSS20Q19 HUB- is packed in a wooden crate. Both composite and rotationally molded containers are optional items.

20.DESCRIPTION: The CAMSS20Q19HUB is a shelter system used to complex multiple CAMSS20Q shelters together. The frame is the same as the other CAMSS20Q shelters. The HUB opens up completely on the both ends and on both ends to allow for easy access between four different shelters. The CAMSS20Q is modular and may be connected to a variety of other CAMSS shelters or other DoD shelters for complete versatility. The CAMSS shelter is compatible with existing military fluorescent lighting systems. Optional lights in accordance with MIL-L-44259 are available. It may be connected to a TEMPER vestibule and it is supported by optional trailer systems with generators and ECUs.

21. SUPPORT	PART NUMBER	Included	DESCRIPTION
EQUIPMENT:	Or NSN	or Optional	
LIGHT SET Product Data Sheet	HIT-20Q-ELC01	Included	Incandescent Light Strings
	HIT-20Q-ELC01-LED	Optional	Light String with LED light bulbs
	HIT-20Q-ELC01-CFL	Optional	Light String with CFL light bulbs
ELECTRICAL OUTLET SET Product Data Sheet	HIT-20Q-ERPL02	Included	Triplex Outlets – Long
	HIT-20Q-ERPS02	Included	Triplex Outlets – Short
EL CODINO			
FLOORING Product Data Sheet	CAMSS20Q-PFL01	Included	Fabric floor with cutouts for base stubs and Velcro to attach to cover
	CAMSS-HFLD/SF	Optional	hard plastic flooring
HEATER			

Product Data Sheet					
AIR CONDITIONER Product Data Sheet	CAMSS-5TECU01 Optional		Five ton ECU with 12kw of heating		
	CAMSS-2.5TECU01	Optional	2.5 ton ECU with 12kw of heating		
GENERATOR Product Data Sheet	CAMSS-G20KW	Optional	20Kw Generator		
POWER DISTRIBUTION Product Data Sheet	CAMSS-E2SPDS	l Optional	Two shelter power distribution system		
TRAILER	CAMSS-LTT-LE	Optional	CAMSS Light Tactical Trailer System		
MOUNTED SUPPORT SYSTEM Product Data Sheet					
INSULATED LINER Product Data Sheet	CAMSS20Q-HLLE	Optional	CAMSS Insulcam liner system installs quickly and easily like the basic liner system and reduces demand on ECUs by 42%		
INSULATED FLOORING Product Data Sheet					
SOLAR SHADE/ CAMOU. NETT Product Data Sheet	CAMSS20Q-PSF01	Optional	CAMSS Solar Fly is a unique fly system that slides over the cov and reduces solar load on the shelter.		